



NO	Items	Specs
1	Impedance	75Ω
2	Frequency	DC~12 GHz
3	V.S.W.R	1.5 Max
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 1.5mΩ Outer contact ≤ 1.0mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Contact	P.H Bronze	Gold
3	Insulator	Teflon	-
4	Joint Cover	Brass	Nickel
5	Nut	Brass	Nickel
6	Washer	Brass	Nickel

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4

ROHS COMPLIANT

COSMTEC **COSMTEC RESOURCES CO., LTD**

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No. B-055-GF-1-75-12G

Title: BNC JACK SOLDER BULKHEAD
EDGE MOUNT12G-SDI 75Ω

DATE: FEB/10/2022 SCALE: 1:1 UNIT m/m REV A