



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~6GHz
3	V.S.W.R	-
4	PIM	-
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	2300V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact 0.4mΩ Max. Outer contact 0.2mΩ Max.
8	Temperture Range	-55°C ~ +165°C
9	Mating	Screw-On / 500 Cycles
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	CuSnZn
3	Body	Brass	CuSnZn
4	SQ. Body	Brass	CuSnZn
5	Body	Brass	CuSnZn
6	Contact	P.H Bronze	CuSnZn
7	Insulator	Teflon	-
8	Contact	P.H Bronze	CuSnZn
9	Insulator	Teflon	-
10	Contact	P.H Bronze	CuSnZn
11	Insulator	Teflon	-
12	Contact	Brass	CuSnZn
13	Cover Nut	Brass	CuSnZn

*Dimensions Are In Millimeters Unless Otherwise Specified Tolerances*

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4

**ROHS COMPLIANT**

**COSMTEC** **COSMTEC RESOURCES CO.,LTD**

DRAFT      CHECKED      APPROVED

The Drawing Contans Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. [www.cosmtec.com](http://www.cosmtec.com)

Part No.	DN-046		
Title:	7-16 DIN JACK TO JACK TO JACK T-TYPE ADAPTER		
DATE:	FEB/18/2022	SCALE:	1:1
UNIT	m/m	REV	A