



NO	Items	Specs
1	Impedance	75Ω
2	Frequency	DC~12 GHz
3	V.S.W.R	1.5 Max
4	Working Voltage	175V
5	Dielectric Withstanding Voltage	AC 500V
6	Insulation Resistance	500 MΩ Min
7	Contact Resistance	Center contact ≤ 10mΩ Outer contact ≤ 5mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Push-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Gold
2	Contact	BeCu	Gold
3	Insulator	Teflon	-
4	Nut	Brass	Nickel

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4

ROHS COMPLIANT

COSMTEC **COSMTEC RESOURCES CO., LTD**

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No.	HB-006		
Title:	MICRO HD BNC JACK BULKHEAD SOLDER EDGE MOUNT (12G)		
DATE:	FEB/14/2022	SCALE:	1:1
UNIT	m/m	REV	A