



NO	Description	Material	Finish
1	Body	Brass	CuSnZn
2	Shell	Brass	CuSnZn
3	Contacter	Brass	CuSnZn
4	Ground	P.H Bronze	CuSnZn
5	Insulator	Teflon	-
6	Ground	Brass	CuSnZn
7	Snap Ring	SUS304	-
8	Gasket	Silicone	-

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4



COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com

NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~6GHz
3	V.S.W.R	1.20 Max
4	PIM	-155dBc Max.
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	1500V
6	Insulation Resistance	3000 MΩ Min
7	Contact Resistance	Center contact ≤ 2mΩ Outer contact ≤ 1mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On / 500 Cycles
10	Material/Finish	All RoHS Compliant

Part No. MD54-011

Title: 4.3-10 DIN JACK - N PLUG

DATE: JAN/26/2023 SCALE: 1:1 UNIT: m/m REV: A