



| NO | Items | Specs |
|----|---------------------------------|---|
| 1 | Impedance | 50Ω |
| 2 | Frequency | DC~6GHz |
| 3 | V.S.W.R | 1.20 Max |
| 4 | PIM | -155dBc Max. |
| 4 | Working Voltage | 500V |
| 5 | Dielectric Withstanding Voltage | 1500V |
| 6 | Insulation Resistance | 3000 MΩ Min |
| 7 | Contact Resistance | Center contact ≤ 2mΩ Outer contact ≤ 1mΩ |
| 8 | Temperture Range | -55°C ~ +165°C |
| 9 | Mating | Screw-On / 500 Cycles |
| 10 | Material/Finish | All RoHS Compliant |

| NO | Description | Material | Finish |
|----|-------------|------------|--------|
| 1 | Body | Brass | CuSnZn |
| 2 | Body | Brass | CuSnZn |
| 3 | Insulator | Teflon | - |
| 4 | Contactator | P.H Bronze | CuSnZn |

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances

| | |
|-----------|---------|
| 0.5-6 | = ± 0.2 |
| 6-30 | = ± 0.4 |
| 30-120 | = ± 0.6 |
| 120-315 | = ± 1.0 |
| 315-1000 | = ± 1.6 |
| 1000-2000 | = ± 2.4 |

ROHS COMPLIANT

COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contans Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

| | | | | |
|----------|----------------------------|--------|-----|------|
| Part No. | MMN-013 | | | |
| Title: | 2.2-5 PLUG TO PLUG ADAPTER | | | |
| DATE: | SEP/07/2022 | SCALE: | 1:1 | UNIT |
| | | | m/m | REV |
| | | | | A |