



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~26.5 GHz
3	V.S.W.R	1.3 Max
4	Working Voltage	325V
5	Dielectric Withstanding Voltage	AC 500V
6	Insulation Resistance	5 GΩ Min
7	Contact Resistance	Center contact ≤ 6.0mΩ Outer contact ≤ 2.0mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Push-Pull
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	BeCu	Gold
2	Contact	BeCu	Gold
3	Insulator	Teflon	-

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No.	MNSP-001-1		
Title:	SMPM JACK TO JACK ADAPTER L:5.3MM		
DATE:	MAR/23/2018	SCALE:	1:1
UNIT	m/m	REV	A