


NO	Description	Material	Finish
1	Body	Brass	Gold
2	Insulator	Teflon	—
3	Contact	Brass	Gold
4	Cap	Brass	Gold
5	Snap Ring	BeCu	Gold
6	Ferrule	Brass	Gold

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances



0.5–6	= ± 0.2
6–30	= ± 0.4
30–120	= ± 0.6
120–315	= ± 1.0
315–1000	= ± 1.6
1000–2000	= ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT	CHECKED	APPROVED
The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com		

NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~6 GHz
3	V.S.W.R	1.3 Max
4	Working Voltage	335V
5	Dielectric Withstanding Voltage	AC 500V
6	Insulation Resistance	500 MΩ Min
7	Contact Resistance	Center contact ≤ 10mΩ Outer contact ≤ 5mΩ
8	Temperture Range	–55°C ~ +165°C
9	Mating	Push–On
10	Material/Finish	All RoHS Compliant

Part No.	MX–002–174		
Title:	MMCX PLUG R/A CRIMP FOR RG–174, RG–316, RG–188		
DATE:	AUG/27/2018	SCALE:	1:1
UNIT	m/m	REV	A