



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~6 GHz
3	V.S.W.R	1.2 Max
4	Working Voltage	335V
5	Dielectric Withstanding Voltage	AC 500V
6	Insulation Resistance	500 MΩ Min
7	Contact Resistance	Center contact ≤ 10mΩ Outer contact ≤ 5mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Push-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Gold
2	Contact	BeCu	Gold
3	Insulator	Teflon	-

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4

ROHS COMPLIANT

COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No. MX-004

Title: MMCX JACK SOLDER FOR PCB

DATE: OCT/31/2019 SCALE: 1:1 UNIT m/m REV A