



RECOMMENDED MOUNTING HOLES

1	Impedance	50Ω
2	Frequency	DC~11GHz
3	V.S.W.R	1.3 Max
4	Working Voltage	1,000V
5	Insulation Resistance	5000 MΩ Min
6	Contact Resistance	Center contact ≤ 2.0mΩ Outer contact ≤ 0.5mΩ
7	Temperture Range	-55°C ~ +165°C
8	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Contact	BeCu	Gold
3	Insulator	Teflon	-
4	Bullet Pin	Brass	Gold
5	Cable Tube	Brass	Gold
5	Nut	Brass	Nickel
6	Washer	Brass	Nickel
7	Gasket	Silicone	-

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT	CHECKED	APPROVED
The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com		

Part No. N-007-086

Title: N JACK BULKHEAD SOLDER FOR .086 CABLE T.G.N.

DATE: APR/20/2021	SCALE: 1:1	UNIT: m/m	REV: A
-------------------	------------	-----------	--------