



RECOMMENDED MOUNTING HOLES

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Contactors	Brass	Gold
3	Insulator	Teflon	-
4	Bullet Pin	Brass	Gold
5	Nut	Brass	Nickel
6	Washer	Brass	Nickel

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4

ROHS COMPLIANT

COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com

1	Impedance	50Ω
2	Frequency	DC~6 GHz
3	V.S.W.R	1.3 Max
4	Working Voltage	1,400V
5	Insulation Resistance	5000 MΩ Min
6	Contact Resistance	Center contact ≤ 2.0mΩ Outer contact ≤ 0.5mΩ
7	Temperature Range	-55°C ~ +165°C
8	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

Part No.	N-007-58-TGN		
Title:	N JACK BULKHEAD CRIMP PIN-IN-PIN FOR RG-58 T.G.N.		
DATE:	NOV/10/2021	SCALE:	1:1
UNIT	m/m	REV	A