



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~6GHz
3	Working Voltage	1000V rms
4	Dielectric Withstanding Voltage	1000V rms
5	Insulation Resistance	5G Ω Min
6	Contact Resistance	Center contact ≤ 2.0mΩ Outer contact ≤ 0.5mΩ
7	Temperture Range	-55°C ~ +165°C
8	Mating	Screw-On
9	Durability	500 Matings
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Insulator	Teflon	-
3	Contact	Brass	Gold

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances

0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4

ROHS COMPLIANT

COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No.	N-011		
Title:	N JACK SOLDER FLANGE MOUNT T.G.N		
DATE:	SEP/16/2013	SCALE:	1:1
UNIT	m/m	REV	A