



NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Shell	Brass	Nickel
3	Insulator	Teflon	-
4	Ground	Brass	Nickel
5	Insulator	Teflon	-
6	Contact	Brass	Gold
7	Snap Ring	SUS304	-
8	Gasket	Silicon	-

*Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances*

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4

ROHS COMPLIANT



COSMTEC RESOURCES CO., LTD

DRAFT	CHECKED	APPROVED
The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com		

NO	Items	Specs
1	Impedance	Unconstant
2	Frequency	DC~300MHz
3	Working Voltage	500V
4	Dielectric Withstanding Voltage	AC 1500V
5	Insulation Resistance	5000 MΩ Min
6	Temperature Range	-55°C ~ +165°C
7	Mating	Screw-On
8	Material/Finish	All RoHS Compliant

Part No.	N-019-TGN		
Title:	N PLUG TO UHF JACK		
DATE:	JUL/21/2018	SCALE:	1:1
UNIT	m/m	REV	A