



1	Impedance	50Ω
2	Frequency	DC~11 GHz
3	V.S.W.R	1.25 Max
4	Working Voltage	1,400V
5	Insulation Resistance	5000 MΩ Min
6	Contact Resistance	Center contact ≤ 2.0mΩ Outer contact ≤ 0.5mΩ
7	Temperture Range	-55°C ~ +165°C
8	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Shell	Brass	Nickel
3	Ground	Brass	Nickel
4	Snap Ring	Steel	-
5	Insulator	Teflon	-
6	Gasket	Silicone	-
7	Contacter	P.H Bronze	Gold

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4



COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No.	N-024		
Title:	N PLUG - PLUG R/A ADAPTER		
DATE:	SEP/22/2014	SCALE:	1:1
UNIT	m/m	REV	A