



| NO | Description | Material | Finish |
|----|-------------|------------|--------|
| 1 | Body | Brass | Nickel |
| 2 | Shell | Brass | Nickel |
| 3 | Ground | Brass | Nickel |
| 4 | Snap Ring | Steel | - |
| 5 | Insulator | Teflon | - |
| 6 | SQ. Body | Brass | Nickel |
| 7 | Joint | Brass | Nickel |
| 8 | Insulator | Teflon | - |
| 9 | Gasket | Silicone | - |
| 10 | Contactors | P.H Bronze | Gold |

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances

| |
|-------------------|
| 0.5-6 = ± 0.2 |
| 6-30 = ± 0.4 |
| 30-120 = ± 0.6 |
| 120-315 = ± 1.0 |
| 315-1000 = ± 1.6 |
| 1000-2000 = ± 2.4 |



COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No. N-025

Title: N PLUG - JACK R/A ADAPTER

DATE: NOV/21/2017 SCALE: 1:1 UNIT: m/m REV: A

| | | |
|----|-----------------------|---|
| 1 | Impedance | 50Ω |
| 2 | Frequency | DC~11 GHz |
| 3 | V.S.W.R | 1.25 Max |
| 4 | Working Voltage | 1,400V |
| 5 | Insulation Resistance | 5000 MΩ Min |
| 6 | Contact Resistance | Center contact ≤ 2.0mΩ Outer contact ≤ 0.5mΩ |
| 7 | Temperture Range | -55°C ~ +165°C |
| 8 | Mating | Screw-On |
| 10 | Material/Finish | All RoHS Compliant |