





NO	Description	Material	Finish
1	Shell	Brass	Nickle
2	Body	Brass	Nickle
3	Insulator	Teflon	-
4	Contact	Brass	Gold
5	Ground	Brass	Nickle
6	Cable Tube	Brass	Nickle
7	Nut Cover	Brass	Nickle
8	Ferrule	Brass	Nickle
9	Snap Ring	Steel	-
10	Gasket	Silicone	-

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances



0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT

CHECKED

APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

1	Impedance	50Ω
2	Frequency	DC~6 GHz
3	V.S.W.R	1.3 Max
4	Working Voltage	1,400V
5	Insulation Resistance	5000 MΩ Min
6	Contact Resistance	Center contact ≤ 2.0mΩ
		Outer contact ≤ 0.5mΩ
7	Temperature Range	-55°C ~ +165°C
8	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

Part No. N-042-H-58

Title: N PLUG R/A CRIMP FOR
RG-58, LMR195, LMR200

DATE: MAR/10/2020

SCALE: 1:1

UNIT m/m

REV A