



Note:
Do Turn Male (Plug) Connector Nut (Shell)
Only To Tighten

NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~12GHz
3	V.S.W.R	1.2 Max
4	Working Voltage	335V
5	Dielectric Withstanding Voltage	1000V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 2.5mΩ Outer contact ≤ 3.0mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On / Push-pull
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Contactors	P.H Bronze	CuSnZn
3	Insulator	Teflon	—

Dimensions Are In Millimeters Unless Otherwise Specified Tolerances

0.5-6 = ± 0.2	
6-30 = ± 0.4	
30-120 = ± 0.6	
120-315 = ± 1.0	
315-1000 = ± 1.6	
1000-2000 = ± 2.4	

COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. Specifications are subject to change without prior notice. Cosmtec Resource Co., Ltd All Rights Reserved, E & OE www.cosmtec.com

Part No.		Q-011	
Title: QMA JACK- N JACK ADAPTER			
DATE:	SCALE:	UNIT	REV
FEB/23/2022	1:1	m/m	A