



NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Shell	Brass	Nickel
3	Clip	P.H Bronze	Nickel
4	Insulator	Teflon	-
5	Contactors	P.H Bronze	Gold
6	Insulator	Teflon	-

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT	CHECKED	APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~12.5GHz
3	V.S.W.R	1.25 Max
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 3.0mΩ Outer contact ≤ 2.0mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

Part No.	Q-012		
Title:	QMA PLUG TO SMA JACK ADAPTER		
DATE:	AUG/23/2022	SCALE:	1:1
UNIT	m/m	REV	A