



Note:
Do Turn Male (Plug) Connector Nut (Shell)
Only To Tighten

NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~12GHz
3	V.S.W.R	1.25 Max
4	Working Voltage	335V
5	Dielectric Withstanding Voltage	1000V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 2.5mΩ Outer contact ≤ 3.0mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On / Push-pull
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Contact	Brass	CuSnZn
3	Insulator	Teflon	-
4	Shell	Brass	Nickel
5	Snap Ring	SUS304	-
6	Gasket	Silicone	-
7	Shell	Brass	Nickel
8	Ground	P.H Bronze	Nickel

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT

CHECKED

APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission.
Specifications are subject to change without prior notice. Cosmtec Resource Co., Ltd
All Rights Reserved, E & OE
www.cosmtec.com

Part No.

Q-022

Title:

QMA PLUG - N PLUG ADAPTER

DATE:

FEB/23/2022

SCALE:

1:1

UNIT

m/m

REV

A