



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~12.5 GHz
3	V.S.W.R	1.3 Max
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 3.0mΩ Outer contact ≤ 2.0mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Gold
2	Contact	P.H Bronze	Gold
3	Insulator	Teflon	-
4	Nut	Brass	Gold
5	Washer	Brass	Gold

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4

ROHS COMPLIANT

COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission.
Specifications are subject to change without prior notice. Cosmtec Resource Co., Ltd
All Rights Reserved, E & OE www.cosmtec.com

Part No. S-004

Title: SMA JACK BULKHEAD SOLDER CUP
TERMINAL SOLDER ATTACHMENT

DATE: SEP/19/2017 SCALE: 1:1 UNIT: m/m REV: A