



NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Insulator	Teflon	-
3	Contacter	Brass	Gold
4	Body	Brass	Nickel
5	Contacter	P.H Bronze	Gold
6	Shell	Brass	Nickel
7	Snap Ring	Brass	-

*Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances*

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4



COSMTEC **COSMTEC RESOURCES CO., LTD**

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

NO	Items	Specs
1	Impedance	-
2	Frequency	DC~300MHz
3	V.S.W.R	-
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	-
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

Part No.	S-017		
Title:	SMA JACK-UNF PLUG ADAPTER		
DATE:	MAY/04/2022	SCALE:	1:1
UNIT	m/m	REV	A