



NO	Description	Material	Finish
1	Shell	Brass	Nickel
2	Body	Brass	Nickel
3	Ground	Brass	Nickel
4	Body	Brass	Nickel
5	Contactors	P.H Bronze	Gold
6	Snap Ring	Stainless	-
7	Gasket	Silicone	-

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4



COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com

NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~18GHz
3	V.S.W.R	1.25 Max
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 3.0mΩ Outer contact ≤ 2.0mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

Part No. S-022

Title: SMA JACK - N PLUG ADAPTER

DATE: MAY/22/2011 SCALE: 1:1 UNIT: m/m REV: A