



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~18GHz
3	V.S.W.R	1.25 Max
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 3.0mΩ Outer contact ≤ 2.0mΩ
8	Temperture Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Gold
2	Contactior	P.H Bronze	Gold
3	Insulator	Teflon	-
4	Insulator	Teflon	-
5	Nut	Brass	Gold
6	Washer	Brass	Gold
7	Gasket	Silicone	-

Dimensions Are In Millimeters  
Unless Otherwise Specified  
Tolerances

0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4

**ROHS COMPLIANT**

### PCB MOUNTING HOLES



COSMTEC RESOURCES CO.,LTD

DRAFT      CHECKED      APPROVED

The Drawing Contans Information That Is Proprietary To Cosmtec Resources Co., Ltd  
And Should Not Be Used Without Written Permission.      www.cosmtec.com

Part No.      S-036-16

Title:      SMA JACK SOLDER BULKHEAD FOR PCB MOUNT

DATE:      AUG/26/2020      SCALE:      1:1      UNIT      m/m      REV      B