



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~18GHz
3	V.S.W.R	1.25 Max
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 3.0mΩ Outer contact ≤ 2.0mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Gold
2	Contact	BeCu	Gold
3	Insulator	Teflon	-

Dimensions Are In Millimeters  
Unless Otherwise Specified  
Tolerances

0.5-6 = ± 0.2  
6-30 = ± 0.4  
30-120 = ± 0.6  
120-315 = ± 1.0  
315-1000 = ± 1.6  
1000-2000 = ± 2.4

**ROHS COMPLIANT**

**COSMTEC** COSMTEC RESOURCES CO.,LTD

DRAFT      CHECKED      APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission.      www.cosmtec.com

Part No. S-036-20

Title: SMA JACK SOLDER FOR PCB MOUNT

DATE: MAR/04/2021      SCALE: 1:1      UNIT: m/m      REV: A