



Note:
Do Turn Male (Plug) Connector Nut (Shell)
Only To Tighten

NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~18GHz
3	V.S.W.R	1.25 Max
4	Temperature Range	-55°C ~ +165°C
5	Mating	Screw-On
6	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Contactors	BeCu	Gold
3	Body	Brass	Nickel
4	Insulator	Teflon	—

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances

0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT	CHECKED	APPROVED
The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. Specifications are subject to change without prior notice. Cosmtec Resource Co., Ltd All Rights Reserved, E & OE		
www.cosmtec.com		

Part No.	S-045		
Title:	SMA JACK - N JACK FLANGE MOUNT ADAPTER		
DATE:	SCALE:	UNIT	REV
MAR/21/2017	1:1	m/m	A