




NO	Description	Material	Finish
1	Shell	Brass	Gold
2	Body	Brass	Gold
3	Clip	P.H Bronze	Gold
4	Insulator	Teflon	—
5	Contact	Brass	Gold
6	Insulator	Teflon	—
7	Anti Ring	P.H Bronze	Gold

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances



0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT	CHECKED	APPROVED
The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com		

NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~18GHz
3	V.S.W.R	1.25 Max
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 3.0mΩ Outer contact ≤ 2.0mΩ
8	Temperture Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

Part No.	S-054-Q-B-RP		
Title:	SMA PLUG QUICK TO JACK RP ADAPTER T.G.G.		
DATE:	DEC/25/2015	SCALE:	1:1
UNIT	m/m	REV	A