



NO	Description	Material	Finish
1	Body	Brass	Gold
2	Insulator	Teflon	-
3	Contact	BeCu	Gold
4	Insulator	Teflon	-
5	Shell	Brass	Gold
6	Snap Ring	Stainless	Passivated
7	Gasket	Silicone	-

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4

ROHS COMPLIANT



COSMTEC RESOURCES CO., LTD

DRAFT

CHECKED

APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No. S-054-RP-1-18HP

Title: SMA PLUG RP - JACK RP ADAPTER

DATE: NOV/17/2016

SCALE: 1:1

UNIT m/m

REV A

NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~18GHz
3	V.S.W.R	1.25 Max
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 3.0mΩ Outer contact ≤ 2.0mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant