



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~4GHz
3	V.S.W.R	1.5 Max
4	Dielectric Withstanding Voltage	750V
5	Contact Resistance	Center contact ≤ 5mΩ Outer contact ≤ 2.5mΩ
6	Temperture Range	-55°C ~ +165°C
7	Durability	500 Matings
8	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	SQ. Body	Brass	Gold
2	Body	Brass	Gold
3	Contactior	Brass	Gold
4	Insulator	Teflon	-
5	Insulator	Teflon	-

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances



TOLERANCE:
X ±0.1
X.X ±0.05
X.XX ±0.02
ANGULAR ±0.5°



COSMTEC RESOURCES CO.,LTD

DRAFT	CHECKED	APPROVED

The Drawing Contans Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No.	SB-007-1		
Title:	SMB JACK SOLDER R/A FOR PCB T.G.G.		
DATE:	NOV/25/2009	SCALE:	1:1
UNIT	m/m	REV	A