



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~4GHz
3	V.S.W.R	1.3 Max
4	Working Voltage	335V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	500 MΩ Min
7	Contact Resistance	Center contact ≤ 5.0mΩ Outer contact ≤ 2.5mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Push-Pull
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Gold
2	Contactors	Brass	Gold
3	Insulator	Teflon	-

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

X ±0.1
X.X ±0.05
X.XX ±0.02
ANGULAR ±0.5°



COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No.	SB-019-4		
Title:	SMB JACK (MALE PIN) SOLDER EDGE MOUNT FOR PCB		
DATE:	JAN/20/2022	SCALE:	1:1
UNIT	m/m	REV	A