




NO	Items	Specs
1	Impedance	50 Ω
2	Frequency	DC~6GHz
3	V.S.W.R	1.3 Max
4	Working Voltage	335V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	1000 M Ω Min
7	Contact Resistance	Center contact $\leq 5.0m\Omega$ Outer contact $\leq 2.5m\Omega$
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Shell	Brass	Gold
2	Body	Brass	Gold
3	Contact	P.H Bronze	Gold
4	Insulator	Teflon	-
5	Ferrule	Brass	Gold

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances



0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT	CHECKED	APPROVED
The Drawing Contains Information That Is Proprietary To Cosmtect Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtect.com		

Part No.	SC-001-316D		
Title:	SMC PLUG CRIMP FOR RG-316D, K02250D		
DATE:	NOV/16/2016	SCALE:	1:1
UNIT	m/m	REV	A