



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~6GHz
3	V.S.W.R	1.3 Max
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 1.5mΩ Outer contact ≤ 1.0mΩ
8	Temperture Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Insulator	Teflon	—
3	Contactior	Brass	Gold
4	Cable Tube	Brass	Nickel
5	Buleet Pin	Brass	Gold
6	Ferrule	Brass	Nickel

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances



0.5—6	= ± 0.2
6—30	= ± 0.4
30—120	= ± 0.6
120—315	= ± 1.0
315—1000	= ± 1.6
1000—2000	= ± 2.4



COSMTEC RESOURCES CO.,LTD

DRAFT	CHECKED	APPROVED
The Drawing Contans Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com		

Part No.	T-008-58-TGN		
Title:	TNC JACK CRIMP FOR RG-58		
DATE:	OCT/31/2022	SCALE:	1:1
UNIT	m/m	REV	A