



1	Impedance	50 Ω
2	Frequency	DC~11 GHz
3	V.S.W.R	1.3 Max
4	Working Voltage	500V
5	Insulation Resistance	5000 M Ω Min
6	Contact Resistance	Center contact $\leq 1.5m\Omega$ Outer contact $\leq 0.2m\Omega$
7	Temperature Range	-55°C ~ +165°C
8	Mating	Screw-On
9	Waterproof Level	IP67 Unmated
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Insulator	Teflon	-
3	Insulator	Teflon	-
4	Contact	Brass	Gold
5	Nut	Brass	Nickel
6	Washer	Brass	Nickel

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4

ROHS COMPLIANT

COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No.	T-019-TGN			
Title:	TNC JACK BULKHEAD TO JACK ADAPTER			
DATE:	JUL/31/2019	SCALE:	1:1	UNIT
			m/m	REV
				A