




.028" / 0.75mm
Hex. Crimp Tool



NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Insulator	Teflon	-
3	Contact	Brass	Gold
4	Bullet Pin	Brass	Gold
5	Shell	Brass	Nickel
6	Snap Ring	Brass	-
7	Ferrule	Brass	Nickel

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT

CHECKED

APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

NO	Items	Specs
1	Impedance	-
2	Frequency	DC~300MHz
3	V.S.W.R	-
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	-
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

Part No. U-005-174 (M-TYPE)

Title: UHF PLUG CRIMP FOR
RG-174, RG-316 (M16P1.0)

DATE: FEB/07/2023

SCALE: 1:1

UNIT: m/m

REV: A