




NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Shell	Brass	Nickel
3	Shell	Brass	Nickel
4	Contact	Brass	Gold
5	Insulator	Teflon	—
6	Insulator	Teflon	—
7	Snap Ring	Brass	—
8	Snap Ring	Brass	—

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances



0.5–6 = ± 0.2
6–30 = ± 0.4
30–120 = ± 0.6
120–315 = ± 1.0
315–1000 = ± 1.6
1000–2000 = ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT

CHECKED

APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

NO	Items	Specs
1	Impedance	—
2	Frequency	DC~300MHz
3	V.S.W.R	—
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	—
8	Temperture Range	–55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

Part No. U-010 (M-TYPE)

Title: UHF PLUG TO PLUG ADAPTER
(M16P1.0)

DATE: FEB/15/2023	SCALE: 1:1	UNIT: m/m	REV: A
-------------------	------------	-----------	--------