







NC	ltems	Specs
1	Impedance	1
2	Frequency	DC~300MHz
3	V.S.W.R	ı
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	I
		ı
8	Temperture Range	−55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

ИО	Description	Material	Finish
1	Body	Brass	Nickel
2	Insulator	Teflon	_
3	Contactor	Brass	Gold
4	Insulator	Teflon	_
5	Nut	Brass	Nickel
6	Washer	Brass	Nickel
7	Nut	Brass	Nickel

Dimensions Are In Millimeters Unless Otherwise Specified Tolerances

ROHS COMPLIANT

ers	0.5-6	=	±	0.2
	6-30	=	±	0.4
	30-120	=	±	0.6
	120-315	=	±	1.0
	315-1000	=	±	1.6
1	000-2000	=	±	2.4

© COSMTEC	COSMTEC RESOURCES CO.,LTD	
DRAFT	CHECKED	APPROVED

DRAFT CHECKED APPROVED

The Drawing Contans Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No. U-012 (M-TYPE)

Title: UHF JACK TO JACK ADAPTER
(M16P1.0)

DATE: SCALE: UINT FEB/15/2023 1:1 m/m