



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~6 GHz
3	V.S.W.R	1.2 Max
4	Working Voltage	225V
5	Dielectric Withstanding Voltage	AC 500V
6	Insulation Resistance	500 MΩ Min
7	Contact Resistance	Center contact ≤ 10mΩ Outer contact ≤ 5mΩ
8	Temperture Range	-55°C ~ +165°C
9	Mating	Screw/Push-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Gold
2	Body	P.H. Bronze	Gold
3	Insulator	Teflon	-
4	Contactora	BeCu	Gold
5	Insulator	Teflon	-

Dimensions Are In Millimeters Unless Otherwise Specified

Tolerances	Dimensions
± 0.2	0.5-6
± 0.4	6-30
± 0.6	30-120
± 1.0	120-315
± 1.6	315-1000
± 2.4	1000-2000

ROHS COMPLIANT

COSMTEC **COSMTEC RESOURCES CO.,LTD**

DRAFT CHECKED APPROVED

The Drawing Contans Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No.	X-051		
Title:	MCX PLUG - SMA JACK ADAPTER		
DATE:	NOV/17/2016	SCALE:	1:1
UNIT	m/m	REV	A